

Norfield




norfield.com

800-824-6242

2400ASR AUTO DOUBLE-PREP STRIKE ROUTER

AUTOMATIC CNC MACHINE FOR HIGH OUTPUT OF INTERIOR & EXTERIOR STRIKE JAMBS AND BALL CATCH HEAD JAMBS




Throughput Rate

Single Prep
4-5
jamb/minute

Double Prep
3-4
jamb/minute



Easy to operate: Intuitive, graphical touchscreen enables quick, easy selection of functions.



High Frequency Router Motor is quiet, durable, and long lasting.



Increased Safety: heavy steel enclosure and double hand sensors keeps operator's hands away from moving parts.



Save Labor: High speed cycle allows strike jamb prep on a door production line, or the 2400 can be an independent high-volume workstation.

product	process	specs	features	options
2400 Automatic Strike Jamb Router for single or double preps		Strike plate size 1/2" to 8" Pocket size 3/4" x 3/4" to 1" x 1" Pocket depth Adjustable to 3/4" Jamb length 70" to 96" Jamb width 2-1/2" to 10-1/2" Jamb thickness 3/8" to 1-1/2" Electrical 208-230, 3Ph, 60 Hz, 30 Amps Pneumatic 5 cfm @ 90 psi Floor Space req. (min.) 11'W X 5'D x 5'H' Approx. Shipping Wt 800 lbs Vacuum connection 4" duct	<ul style="list-style-type: none"> Jamb types: flat (with or without stop applied); single or double rabbeted; split Strike plate type: No lip, full lip and T-strike Double full lip for ball catch heads 	<ul style="list-style-type: none"> Vacuum for dust collection